

To Market® Fusion™ Commercial Carpet

IN STEP

3844 N. W. 8th Street
 Oklahoma City, OK 73107

1.866.772.4772
www.ToMkt.com

To Market® introduces Fusion™ Commercial Carpet, merging the elements of design and texture into a series of color-coordinated commercial carpets which are engineered to meet the highest standards for both performance and aesthetics. Each Fusion™ Commercial Carpet style offers unlimited design flexibility for end-use applications in office, educational, institutional, healthcare and retail environments.

ENVIRONMENTAL BENEFITS

- Manufactured utilizing environmental safeguards including reclaimed water in the dyeing and manufacturing process
- Contains NO 4PCH or formaldehyde
- Low volatile organic compounds (VOC's)
- To Market accepts products at the end of their life to be reused and recycled in an effort to cut down on landfill waste and reduce the drain on natural resources.

LEED® INFORMATION

Environmental Quality- Each Fusion™ carpet style exceeds the Carpet & Rug Institute 'Green Label Plus' specifications for low VOC's, thereby meeting the LEED requirement for Low-Emitting Materials: carpet. In addition, the recommended adhesive meets SCAQMD Rule #1168 as required by LEED in EQ credit 4.1.

LEED CREDIT	CATEGORY DESCRIPTIONS	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.1 Environmental Quality	Low-Emitting Materials: Adhesives & Sealants	Recommended adhesive meets SCAQMD #1168	1
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials: Carpet	Low-VOC; meets Carpet and Rug Institute's 'Green Label Plus' program	1

SPECIFICATIONS

Product Name:	In Step
Machine:	Patterned Loop
Yarn Content:	XTI® Nylon
Gauge:	1/8th
Stitches Per Inch:	15
Finished Pile Height:	Average .187
Tufted Yarn Weight:	30 Oz. Per Sq. Yard
Yarn Construction:	2 Ply Heatset
Dyeing Process:	Piece Dyed

To Market® Fusion™ Commercial Carpet

IN STEP

Primary Backing:	Woven Polypropylene
Secondary Backing:	ActionBac®
Total Weight:	Approximately 67 Oz. Per Sq. Yard
Pattern Repeat:	12" x 12"
Static Control:	Built-in; Inherent In Fiber System
Soil Retardant:	Royalguard
Density Factor (D):	5,775
Weight Density (WD):	173,262
Flammability Test	Passes–Methenamine Pill Test DOC FF1-70 Passes–Critical Radiant Flux ASTM E-648–Class 1 Passes–Smoke Chamber Test ASTM E-662
CRI Indoor Air Quality#	13600678
Warranty:	10 Year Fiber Wear; 10 Year Anti-static RN 42032 MADE IN THE USA FUSION WITH BIOBAK™ (see below) WARRANTY INFO <ul style="list-style-type: none"> - Ten-year fiber wear warranty - Ten-year static control - Life-of-the-carpet edge ravel - Life-of-the-carpet delamination - Life-of-the-carpet pilling/fuzzing

Please call your local To Market Sales Representative for information on alternative backing system options.

ADDITIONAL BENEFITS

- **BIOBAK™** - In addition to the standard enriched latex backing, FUSION™ Commercial Carpet offers two different types of high-performance polyurethane backing products. Both of these backings are environmentally responsible and the non-woven secondary backing is made of 100% post-consumer materials such as recycled soda bottles.
- Does not support fungus growth or mold, resistant to mildew
- Passes British Spill Test (moisture barrier)